



Arabian United Float Glass Co.
الشركة العربية المتحدة للزجاج المسطح

ARALUX ® CLEAR

Technical Data Sheet **(Mirror)**

Packaging: Wooden case.

Product information:

Thickness	3 mm
Thickness tolerance	+/-0.2
Size	3210x2250
Glass type	Mirror (MRO)
Glass Standard	EN
Appearance	Silver Mirror

Physical Properties:

Silver Layer Thickness	Light Reflectance(%)	Paint Coating Thickness	Paint Adhesion
700mg/m2	>83%	Min 45 Micron	Max Grade 2

Durability:

Resistance to Corrosion		Resistance to Humidity	
Edge Corrosion	After 240hrs. <2.5mm	Edge Corrosion	After 480 hrs. < 0.2 mm
Number of Spots	After 240hrs. 2 of diameter > 0.3mm &< 3mm. 3 of diameter <0.3mm.	Number of Spots	After 480hrs. 1 of diameter <0.3mm



The products in this publication are sold subject to UFG standard terms and conditions of sale and any applicable written warranties will be provided by UFG representative if requested. It is the responsibility of the purchaser to confirm that the products are suitable for their intended application in compliance with the applicable laws and regulations. The performance values shown are nominal and subject to variations due to manufacturing tolerances. A slight shift in visible light reflectance or transmission may be noticed after heat- treatment. Please contact UFG representative to obtain any applicable handling or safety guides and for the most current product information.

Kingdom of Saudi Arabia

Email: Info@aufgc.com

Fax: +966(14)3255444

Tel: +966(14)3255444